



Wan Ceiling/Wall

Designed by Johanna Grawunder, 2005



Halogen - 40W

Wall or ceiling fixture providing direct lighting. Aluminum body, available in shiny white, shiny black and shiny green finishes. Low glare shield. Provided by two different ring due to block the safety tempered glass, in black and green.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

50 mm ШШ 89 ø 115 mm

Main specifications

Mounting	Ceiling and wall surface	
Environments	Indoor dry location	
Light Source Type	Bulb	
Lamp category	Halogen	
Lamp holders	G9	
Ilcos	HSG	
Number of heads	1	
Power (W)	40	

Physical

Colour	vvnite
Length (mm)	115
Net weight (kg)	0.62
Package height (mm)	175
Package width (mm)	220
Package length (mm)	190
Package volume (m3)	0.01
IP internal	40

Download

Nounting instructions	业 PDF
nara Parts	↓ pne

Photometric Files

LDT / IES



Technical Drawings

2D	<u>↓</u> ZIP
3D	⊥ ZIP



















https://professional.flos.com/en/global/product/wan-ceiling-wall-f9550009/

F9550009

Schematic light drawing



Beam Angle:		68°
h(m)	E(lx)	D(m)
1	147	1.35
2	37	2.70
3	16	4.05
4	9	5.40
5	6	6.75

Luminous flux luminaire 460 lm

Photometric

Symmetric

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-250
LED voltage Vf (Vdc)	null
Dimmable	Yes
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No




NOT INCLUDED

RF18863

Halogen Lamp G9 33W 2700K HALOPIN Dimmable

Spare Parts



01.	New type attachment assembly	RF9550300
	with g9 lamp holder and safety	
	ring	
02.	Wan glass assembly	RF9550200
03.	External ring	RF13990
03.	External ring	RF14546
04.	Reflector / ring assembly	RF9550130
04.	Assembly External Ring for Wan	RF9550139

DOWNLOAD









RF9550300

New type attachment assembly with g9 lamp holder and safety ring

DE0550200

Wan glass assembly

RF13990

External ring

RF14546

External ring





RE9550130

Reflector / ring assembly

RF9550139

Assembly External Ring for Wan